











INFORMATIVE NOTE
Read carefully before use

Item 3530	Silicone and cotton palm mitten for trays or pots								
CHARACTERISTICS:	These palm mittens are a Category 2 Personal Protective Equipment (PPE). They have the CE marking as they comply with the requirements of Regulation (EU) 2016/425 and have been certified by the Notified Organization RICOTEST (No. 0498 - Via Tione 9 - 37010 Pastrengo - VR). The compliance with the requirements of the Regulation has been verified through the technical standards EN ISO 21420: 2020, and EN 407: 2020.								
PERFORMANCE:	<p>The palm mitten meets the general requirements of design and manufacture, safety and efficiency according to EN ISO 21420: 2020.</p> <p>According to EN 407: 2020 protective gloves against thermal risks:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Testing</th> <th style="width: 30%;">Level obtained</th> <th colspan="2" style="width: 40%;">Levels required by the regulation</th> </tr> </thead> <tbody> <tr> <td>Contact heat</td> <td>2 (max 42 s polymer material and max 29 s part in fabric, at 250 ° C)</td> <td>Min. 1</td> <td>Max 4</td> </tr> </tbody> </table>	Testing	Level obtained	Levels required by the regulation		Contact heat	2 (max 42 s polymer material and max 29 s part in fabric, at 250 ° C)	Min. 1	Max 4
Testing	Level obtained	Levels required by the regulation							
Contact heat	2 (max 42 s polymer material and max 29 s part in fabric, at 250 ° C)	Min. 1	Max 4						
RECOMMENDED USES:	These palm mittens are suitable for protecting hands (palm and fingers, from contact with pots, pans or hot plates (within the limits of the marked protective levels and the covered area of the palm mitten)								
RISKS:	<p>Suitable for risks of: contact heat.</p> <p>Not suitable for risks of abrasion, cut, perforation, heat and fire (except contact heat), chemical products, cold and for all uses not mentioned in this Informative Note and in particular those that fall under Category 3 of Personal Protective Equipment.</p> <p>Do not use the PPE with liquids of any kind, as these could penetrate through the palm mitten and come into contact with the user's skin. Do not place in direct contact with heat sources (flames, electric plates, etc.) The protection against flames has not been verified.</p>								
WARNING:	The presence of allergenic substances is not known to the manufacturer. Please report any observed cases of hypersensitivity or allergic reaction. In contact with the skin of particularly sensitive persons, any PPE could cause allergic reactions not foreseen by the manufacturer. In such situations it is recommended to consult a doctor immediately.								
IDENTIFICATION AND CHOICE OF A SUITABLE PPE:	The choice of the suitable model must be made according to the specific needs of the workplace and the type of risk. Therefore, it is advisable to check, before use, the suitability of the characteristics of this palm mitten to your needs.								
PRELIMINARY CHECKS AND USE: WARNINGS	Before use, make a visual check of the palm mitten to make sure it is in perfect condition, clean and intact. If it is not intact (visible damage such as unstitching, breakages or soiling) it must be replaced.								
INSTRUCTIONS FOR MAINTENANCE AND EXPIRY DATE:	<p>The palm mitten must be stored in its original packaging, in a dry place away from heat sources. Avoid contact with solvent products that can cause alteration of the characteristics.</p> <p>In particularly severe conditions of use or in environments with special situations, it is possible that the palm mitten undergoes sudden degradation not foreseen by the manufacturer and therefore it is not possible to establish an "expiry date", even if, in relation to the natural deterioration of the material with which this PPE is produced and the consequent reduction in quality, it is considered appropriate to recommend its use no later than 5 years from purchase.</p> <p>Conditions other than those recommended could shorten the life of the product.</p>								
CLEANING	No washing is allowed to prevent the palm mitten from losing its safety features. Remove any dirt with a damp cloth or soft brush.								
MARKING:	<p>On the label sewn on the palm mitten</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 30%; text-align: center;"></td> <td>CE marking, which certifies the compliance of the PPE with the essential health and safety requirements of the Regulation. Name of the manufacturer.</td> </tr> <tr> <td style="text-align: center;">3530</td> <td>Palm mitten model</td> </tr> <tr> <td style="text-align: center;"></td> <td>Pictogram that refers to the Informative Note</td> </tr> <tr> <td style="text-align: center;"></td> <td>Pictogram with batch by production date (week / year)</td> </tr> </tbody> </table>		CE marking, which certifies the compliance of the PPE with the essential health and safety requirements of the Regulation. Name of the manufacturer.	3530	Palm mitten model		Pictogram that refers to the Informative Note		Pictogram with batch by production date (week / year)
	CE marking, which certifies the compliance of the PPE with the essential health and safety requirements of the Regulation. Name of the manufacturer.								
3530	Palm mitten model								
	Pictogram that refers to the Informative Note								
	Pictogram with batch by production date (week / year)								
	<p>EN 407:2020 + pictogram related to thermal risks explained below.</p> <p style="text-align: center;">X 2 X X X X (a) (b) (c) (d) (e) (f)</p> <p>This pictogram indicates that the PPE has been designed for heat and fire hazards and the numbers at the bottom indicate the levels obtained in the laboratory tests and they mean:</p> <p>a) limited flame spread X= characteristic not ascertained</p> <p>b) contact heat 1: ≥ 15s threshold time t_t at 100° C 2: ≥ 15s threshold time t_t at 250° C 3: ≥ 15s threshold time t_t at 350° C 4: ≥ 15s threshold time t_t at 500° C</p> <p>c) convective heat X= characteristic not ascertained</p> <p>d) radiant heat t₂₄ X= characteristic not ascertained</p> <p>e) small splashes of molten metal n. of drops produced at Δ 40°C X= characteristic not ascertained</p> <p>f) large quantities of molten metal: X= characteristic not ascertained</p>								

The EU declaration of conformity is available on the website www.ghidinicipriano.it

